

**CC-765-...**

Network Type : MV

Electronic voltage detector, compact series, 3-10 kV, C end fitting

**Application:**

- Electronic voltage detector for indoor and outdoor use, with high level of shock, vibration and rain resistance.
- Capacitive head technology, ultra compact.
- Broad voltage range, operating frequency 50 and 60 Hz.

**Features:**

- Robust thermoplastic housing.
- Voltage presence signaled by:
  - Flashing red LEDs;
  - Powerful audible signal (67 dB (A)/1.5 m);
  - Visible over 360° with lighting and display.
- Contact electrodes easily interchangeable.

**Composition:**

- Supplied with an end-fitting matching the insulating stick terminal:
  - C: hexagonal 12 mm for sticks with C fitting;
  - K: universal for sticks with K fitting;
  - U: UDI end-fitting with a U shape (55 mm overhang) for sticks with UDI end-fitting.
- CC-765-44/132 & 63/90 versions are supplied with 1 hook-shaped contact electrode Ø 120 mm, Ref. [CC-ANT120](#)
- Supplied in a carrying case.

**Optional accessories:**

- Recommended insulating sticks: [CE-4-21](#) series.



Référence	Description	Voltage range	Frequency	Weight (kg)
	Fitting			
CC-765-3/10-C	C	3 - 10 kV	50 / 60 Hz	0,600