

Standards

IEC 61243-3: 2014, EN
61243-3:2015 / NF
C18-510 / EN 50110-1 /
IEC 61010-1 / IEC
61010-031

MS-917-..

Network Type : LV

Low Voltage detector DETEX

Application:

- Check the presence of voltage.
- Checks voltage levels from 12 to 900 V AC, 1 000 V DC.
- Sound and light continuity for a non-live circuit (threshold of 200 Ω).
- Search for the polarities of a DC circuit.
- Unipolar phase identification.
- For indoor/outdoor use.



Features:

- Fitted with IP2X test lead points with retractable trigger tips.
- Total safety with hazardous voltage indicator light (> 50 V).
- Protection level: IP65/IK06.
- Self test button to discern the verification of the good functioning and the continuity function.
- Completely modular and adjustable to eclipse sockets.
- LED display.

Composition:

- Supplied with soft carrying case and belt loop Ref. [M-87285](#).

Optional accessories:

- 2 test plug adapters to be fixed on IP2X test lead points with retractable trigger tips enabling to target test plugs Ø 4 mm. Ref. [DX-04](#)
- Carrying bag with belt loop, Ref. [M-87285](#).
- Holder, Ref. [M-952325](#).



Référence	Frequency	Weight (kg)
MS-917-PG	50 - 400 Hz	0,21